

Designed by Luis Weisdorf

PRODUCT



COLORS



// Matt White

Item no.:

007-01105

DESCRIPTION

The Turbo Pendant designed by Luis Weisdorf is made of 12 equal aluminium slats, spirally twisted and mounted together, to give the spherical shape of a round ball. All the surfaces are powdercoated in matt white. The fabric wire and the canopy is alway matt white. As an alternative to the canopy a ceiling hook is enclosed in the package. The pendant comes in 2 sizes \emptyset 360 mm and \emptyset 620 mm

VERSION - TURBO PENDANT

- Fabric wire and canopy white:
- Matt White / White inside // RAL 9003 / RAL 9003 // Gloss level 10 / Gloss level 10

VERSION - TURBO PENDANT

Order item - look for part number in the pricelist.

Series contains the following:

TURBO PENDANT Ø360 TURBO PENDANT Ø620

FACTS

 ${\tt MEASUREMENT} - L\,x\,\,W\,x\,H\,mm$

Lamp height: 360 mm

Lamp bottom diameter: ϕ 100 mm

Lamp top diameter: Ø100 mm

Lamp middle diameter: \emptyset 360 mm Wire length, exposed: Approx.. 3800 mm

Wire length, total: Approx. 4000 mm

WEIGHT ITEM - LAMP INCL. WIRE

1845 g

PACKAGING TYPE

Cardboard box

PACKAGING MEASUREMENT - $L\,x\,W\,x\,H\,cm$

L: 41 x W: 41 x H: 41 cm

 $\ WEIGHT\ PACKAGING\ -\ \textit{MATERIAL\ TYPE\ (recycleable)}$

- Polystyrene: 33 g - EPE sheet: 19 g
- PE polybag: 3 g
- PE polybag: 3 g
 Cardboard inside: 266 g
- Cardboard outside: 773 g

WEIGHT PACKAGING - TOTAL

 $1070~\mathrm{g}$

NUMPER OF PARCELS

1 pc



TURBO // PENDANT SMALL Ø360, EU MODEL

THE TURBO COLLECTION

| Designed by Luis Weisdorf | |
|--|---|
| ACCESSORIES | Bulb requirements: |
| | - Socket: E27 base |
| - | - Recommended light source - All fluorescens light bulbs: |
| | Recommended wattage: 15 W |
| ENVIRONMENT | Max. wattage: 20 W |
| | - Recommended light source - Halogen light bulbs: |
| - | - Recommended wattage: 57 V |
| mnomo. | - Max. wattage: 70 W |
| TESTS | |
| | *Lightbulb not included |
| - | |
| CERTIFICATION AND LABELS | *Euro voltage: 230 V |
| CERTIFICATION AND LABELS | *Frequency: 50 Hz |
| CE-certified | *Supply voltage: AC power ~ |
| CE Certifica | *Normally Closed: IP20 |
| SAFETY INSTRUCTIONS | Tromain Globell 12 20 |
| OH ETT HOTRE CITORO | |
| If the cord or other electrical part is damaged, switch of the lamp and do not use it until it is repaired by a | |
| qualified electrician. | |
| The second secon | Class II / Double insulated CE-Mark |
| | F |
| | \ <u>F</u> |
| | Luminaires accepted for mounting on a flammable base |